

Main

Product or component type	Plug
Product destination	Safety switch H(U)363WA/H(U)363DSWA/ H(U)363AWA F 100 A

Complementary

Line Rated Current	100 A
AWG gauge	AWG 4...AWG 1 1 copper
Cable entry	Cable entry 0.875 in (22.22 mm) Cable entry 1.281 in (32.54 mm)
Electrical connection	Plug-in Appleton Powertite
Interlocking type	Electrical
Material	Brass
Maximum Horse Power Rating	40 hp 600 V AC/DC, three phase
Permissible voltage	600 V AC 250 V DC
Product certifications	UL Listed CSA
Surface finish	Epoxy-polyester powder

Environment

Environmental characteristic	Rainproof Corrosion resistance
NEMA degree of protection	NEMA 4X

Ordering and shipping details

Category	00058 - MISC SWITCH ACCESSORIES
Discount Schedule	DE 1
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	CZ

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------